



Laborator 3

Metode de implementare a unei interfete web grafice- Formulare HTML



Elemente formulare:

 = new in HTML5.

Tag	Description
<code><form></code>	Defines an HTML form for user input
<code><input></code>	Defines an input control
<code><textarea></code>	Defines a multiline input control (text area)
<code><label></code>	Defines a label for an <code><input></code> element
<code><fieldset></code>	Groups related elements in a form
<code><legend></code>	Defines a caption for a <code><fieldset></code> element
<code><select></code>	Defines a drop-down list
<code><optgroup></code>	Defines a group of related options in a drop-down list
<code><option></code>	Defines an option in a drop-down list
<code><button></code>	Defines a clickable button
<code><datalist></code>	 Specifies a list of pre-defined options for input controls
<code><keygen></code>	 Defines a key-pair generator field (for forms)
<code><output></code>	 Defines the result of a calculation



Formularele HTML 5 : compuse din elemente <input>, “text” “radio” sau “submit”

Type	Description
<input type="text">	Defines a one-line text input field
<input type="radio">	Defines a radio button (for selecting one of many choices)
<input type="submit">	Defines a submit button (for submitting the form)

Cu elemente “text”

```
<!DOCTYPE html>
<html>
<body>

<form>
  First name:<br>
  <input type="text" name="firstname">
  <br>
  Last name:<br>
  <input type="text" name="lastname">
</form>

<p>Note that the form itself is not visible.</p>

<p>Also note that the default width of a text
input field is 20 characters.</p>

</body>
</html>
```

First name:

Last name:

Note that the form itself is not visible.

Also note that the default width of a text input field is 20 characters.



Cu elemente “radio”

```
<!DOCTYPE html>
<html>
<body>

<form>
  <input type="radio" name="gender" value="male" checked> Male<br>
  <input type="radio" name="gender" value="female"> Female<br>
  <input type="radio" name="gender" value="other"> Other
</form>

</body>
</html>
```

Male
 Female
 Other



Cu elemente “submit”

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  First name:<br>
  <input type="text" name="firstname" value="Mickey">
  <br>
  Last name:<br>
  <input type="text" name="lastname" value="Mouse">
  <br><br>
  <input type="submit" value="Submit">
</form>

<p>If you click the "Submit" button, the form-data will be sent to a
page called "action_page.php".</p>

</body>
</html>
```

First name:

Last name:

If you click the "Submit" button, the form-data will be sent to a page called "action_page.php".



Atributul Action: definește acțiunea la Submit care implicit trimite datele din formular la server într-un document "action_page.php"

```
<form action="action_page.php">
```

Atributul Method : “get” (implicit) sau “post”

- ❑ “get”: pentru nr limitat de date si date insenzitive
- ❑ “post”: pentru nelimitat de date inclusiv date personale

```
<form action="action_page.php" method="get">
```

```
<form action="action_page.php" method="post">
```



Atributul Name: se atribuie fiecărui element `<input>`, dacă lipsește datele corespunzătoare acelui element nu vor fi trimise

<pre><!DOCTYPE html> <html> <body> <form action="action_page.php"> First name:
 <input type="text" value="Pop">
 Last name:
 <input type="text" name="lastname" value="Anca">

 <input type="submit" value="Submit"> </form> <p>If you click the "Submit" button, the form-data will be sent to a page called "action_page.php". </p> <p>Notice that the value of the "First name" field will not be submitted, because the input element does not have a name attribute.</p> </body> </html></pre>	<p>First name: <input type="text" value="Pop"/></p> <p>Last name: <input type="text" value="Anca"/></p> <p><input type="submit" value="Submit"/></p> <p>If you click the "Submit" button, the form-data will be sent to a page called "action_page.php".</p> <p>Notice that the value of the "First name" field will not be submitted, because the input element does not have a name attribute.</p>
--	--



Răspunsul la formularul din exemplul anterior

<pre><!DOCTYPE html> <html> <body> <form action="action_page.php"> First name:
 <input type="text" value="Pop">
 Last name:
 <input type="text" name="lastname" value="Anca">

 <input type="submit" value="Submit"> </form> <p>If you click the "Submit" button, the form-data will be sent to a page called "action_page.php". </p> <p>Notice that the value of the "First name" field will not be submitted, because the input element does not have a name attribute.</p> </body> </html></pre>	<p>Your input was received as:</p> <p><input type="text" value="lastname=Anca"/></p> <p>The server has processed your input and returned this answer.</p> <p>Note: The HTML tutorial will not teach you how servers are processing input. Processing input is explained in our PHP and ASP tutorials.</p>
--	---



Gruparea datelor cu <fieldset> și <legend>

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  <fieldset>
    <legend>Personal information:</legend>
    First name:<br>
    <input type="text" name="firstname" value="Popa">
    <br>
    Last name:<br>
    <input type="text" name="lastname" value="Anca">
    <br><br>
    <input type="submit" value="Trimite">
  </fieldset>
</form>

</body>
</html>
```

Personal information:

First name:

Last name:



Gruparea datelor cu <fieldset> și <legend> : raspuns

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  <fieldset>
    <legend>Personal information:</legend>
    First name:<br>
    <input type="text" name="firstname" value="Popa">
    <br>
    Last name:<br>
    <input type="text" name="lastname" value="Anca">
    <br><br>
    <input type="submit" value="Trimite">
  </fieldset>
</form>

</body>
</html>
```

Your input was received as:

firstname=Popa&lastname=Anca

The server has processed your input and returned this answer.

Note: The HTML tutorial will not teach you how servers are processing input. Processing input is explained in our PHP and ASP tutorials.



Alte atribute ale formularelor

Attribute	Description
accept-charset	Specifies the charset used in the submitted form (default: the page charset).
action	Specifies an address (url) where to submit the form (default: the submitting page).
autocomplete	Specifies if the browser should autocomplete the form (default: on).
enctype	Specifies the encoding of the submitted data (default: is url-encoded).
method	Specifies the HTTP method used when submitting the form (default: GET).
name	Specifies a name used to identify the form (for DOM usage: document.forms.name).
novalidate	Specifies that the browser should not validate the form.
target	Specifies the target of the address in the action attribute (default: _self).



Elementul <select>: definește o listă expandabilă (drop-down list)

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  <select name="cars">
    <option value="volvo">Volvo</option>
    <option value="saab">Saab</option>
    <option value="fiat">Fiat</option>
    <option value="audi">Audi</option>
  </select>
  <br><br>
  <input type="submit">
</form>

</body>
</html>
```





Elemente preselectate cu `<selected>` în `<select>`: definește elementul preselectat dintr-o listă expandabilă (drop-down list)

```
<!DOCTYPE html>
<html>
<body>

<p>You can preselect an option with the selected
attribute.</p>

<form action="action_page.php">
  <select name="cars">
    <option value="volvo">Volvo</option>
    <option value="saab">Saab</option>
    <option value="fiat" selected>Fiat</option>
    <option value="audi">Audi</option>
  </select>
  <br><br>
  <input type="submit">
</form>

</body>
</html>
```

You can preselect an option with the selected attribute.

Fiat ▼

Trimite



Element `<textarea>`: definește un câmp format din mai multe linii text

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  <textarea name="message" rows="10"
  cols="30">Descrieți serviciile
  solicitate.</textarea>
  <br>
  <input type="submit">
</form>

</body>
</html>
```

Descrieți serviciile solicitate.

Trimite

Completare text în formular

Descrieți serviciile solicitate.

Servicii web:
-email
-agent interfață
-administrare web

Trimite

Răspuns după click pe "Trimite"

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  <textarea name="message" rows="10"
  cols="30">Descrieți serviciile
  solicitate.</textarea>
  <br>
  <input type="submit">
</form>

</body>
</html>
```

Your input was received as:

message=Descrieți serviciile solicitate. Servicii web: -email -agent interfață -administrare web

The server has processed your input and returned this answer.

Note: The HTML tutorial will not teach you how servers are processing input. Processing input is explained in our PHP and ASP tutorials.



Element <button>: definește un buton acționat cu click


```
<!DOCTYPE html>
<html>
<body>

<button type="button" onclick="alert('Hello World!')">Click Me!
</button>

</body>
</html>
```



Răspuns după click pe butonul "Click Me!": afișarea unei ferestre pop-up



Elemente noi HTML 5:

❑ <datalist>: specifică o listă de opțiuni predefinite pentru un element <input>

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  <input list="browsers" name="browser">
  <datalist id="browsers">
    <option value="Internet Explorer">
    <option value="Firefox">
    <option value="Chrome">
    <option value="Opera">
    <option value="Safari">
  </datalist>
  <input type="submit">
</form>

<p><b>Note:</b> The datalist tag is not supported in Safari or IE9 (and earlier).</p>

</body>
</html>
```



Your input was received as:

Răspuns la selectarea "Chrome"

The server has processed your input and returned this answer.

Note: The HTML tutorial will not teach you how servers are processing input. Processing input is explained in our PHP and ASP tutorials.



Elemente noi HTML 5:

- ❑ **<keygen>**: ofera posibilitatea de a autentifica utilizatorii specificand un camp cu o pereche de chei (una privata memorata local si una publica trimisa la server)

<pre><!DOCTYPE html> <html> <body> <form action="action_page.php"> Username: <input type="text" name="user">

 Encryption: <keygen name="security">

 <input type="submit"> </form> </body> </html></pre>	<p>Username: <input type="text" value="Laura"/></p> <p>Encryption: <input type="text" value="2048 (nivel ridicat)"/></p> <p><input type="submit" value="Trimite"/></p>
---	--



Elemente noi HTML 5:

- ❑ **<output>**: ofera rezultatul unui calcul al unei expresii

<pre><!DOCTYPE html> <html> <body> <form action="action_page.php" oninput="x.value=parseInt(a.value)+parseInt(b.value)"> 0 <input type="range" id="a" name="a" value="50"> 100 + <input type="number" id="b" name="b" value="50"> = <output name="x" for="a b"></output>

 <input type="submit"> </form> </body> </html></pre>	<p>0 <input type="range" value="50"/> 100 + <input type="number" value="50"/> = 91</p> <p><input type="submit" value="Trimite"/></p>
---	--



Tipuri de elemente <input>:

❑ **type text** : defineste input o linie de text

<pre><!DOCTYPE html> <html> <body> <form action="action_page.php"> First name:
 <input type="text" name="firstname">
 Last name:
 <input type="text" name="lastname">

 <input type="submit"> </form> <p>Note that the form itself is not visible.</p> <p>Also note that the default width of a text field is 20 characters. </p> </body> </html></pre>	<p>First name: <input type="text"/></p> <p>Last name: <input type="text"/></p> <p><input type="submit" value="Trimite"/></p> <p>Note that the form itself is not visible.</p> <p>Also note that the default width of a text field is 20 characters.</p>
---	---



Tipuri de elemente <input>:

❑ **type password**: defineste input o parola

<pre><!DOCTYPE html> <html> <body> <form action=""> User name:
 <input type="text" name="userid">
 User password:
 <input type="password" name="psw"> </form> <p>The characters in a password field are masked (shown as asterisks or circles).</p> </body> </html></pre>	<p>User name: <input type="text"/></p> <p>User password: <input type="password"/></p> <p>The characters in a password field are masked (shown as asterisks or circles).</p>
--	---



Tipuri de elemente <input>:

- ❑ **type Submit:** definește un buton pentru trimiterea unui formular către un form-handler.

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
First name:<br>
<input type="text" name="firstname" value="Pop">
<br>
Last name:<br>
<input type="text" name="lastname" value="Anca">
<br><br>
<input type="submit" value="Submit">
</form>

<p>If you click "Submit", the form-data will be
sent to a page called "action_page.php".</p>

</body>
</html>
```

First name:

Last name:

If you click "Submit", the form-data will be sent to a page called "action_page.php".

Raspuns dupa click Submit

Your input was received as:

firstname=Pop&lastname=Anca

The server has processed your input and returned this answer.



Tipuri de elemente <input>:

- ❑ **type Reset:** resetează toate valorile formularului la valorile implicite

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
First name:<br>
<input type="text" name="firstname"
value="Popa">
<br>
Last name:<br>
<input type="text" name="lastname"
value="Anca">
<br><br>
<input type="submit" value="Submit">
<input type="reset">
</form>

<p>If you change the input values and then
click the "Reset" button, the form-data will
be reset to the default values.</p>

</body>
</html>
```

First name:

Last name:

If you change the input values and then click the "Reset" button, the form-data will be reset to the default values.

Dca schimb datele

First name:

Last name:

Raspuns dupa click Reseteaza:

First name:

Last name:




Tipuri de elemente `<input>`:

❑ **type Radio:** definește un buton tip Radio

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
  <input type="radio" name="gender"
value="male" checked> Male<br>
  <input type="radio" name="gender"
value="female"> Female<br>
  <input type="radio" name="gender"
value="other"> Other<br><br>
  <input type="submit">
</form>

</body>
</html>
```




Tipuri de elemente `<input>`:

❑ **type CheckBox:** definește un buton tip CheckBox

```
<!DOCTYPE html>
<html>
<body>

<form action="action_page.php">
<input type="checkbox" name="vehicle1"
value="Bike">I have a bike
<br>
<input type="checkbox" name="vehicle2"
value="Car">I have a car
<br><br>
<input type="submit">
</form>

</body>
</html>
```





Tipuri de elemente `<input>`:

□ **type Button:** definește un buton

```
<!DOCTYPE html>
<html>
<body>

<input type="button" onclick="alert('Hello
World!')" value="Click Me!">

</body>
</html>
```



Alte tipuri noi `<input>` în HTML 5:

- color
- date
- datetime
- datetime-local
- email
- month
- number
- range
- search
- tel
- time
- url
- week



Tipuri de elemente <input>:

type number: definește un câmp de tip numeric

```
<!DOCTYPE html>
<html>
<body>

<p>Numeric restrictions will apply in the
input field:</p>

<form action="action_page.php">
  Quantity (between 1 and 5):
  <input type="number" name="quantity"
min="1" max="5">
  <input type="submit">
</form>

<p><b>Note:</b> type="number" is not
supported in IE9 and earlier.</p>

</body>
</html>
```

Numeric restrictions will apply in the input field:

Quantity (between 1 and 5):

Note: type="number" is not supported in IE9 and earlier.



Restricții pentru elementele <input>:

Attribute	Description
disabled	Specifies that an input field should be disabled
max	 Specifies the maximum value for an input field
maxlength	Specifies the maximum number of character for an input field
min	 Specifies the minimum value for an input field
pattern	 Specifies a regular expression to check the input value against
readonly	Specifies that an input field is read only (cannot be changed)
required	 Specifies that an input field is required (must be filled out)
size	Specifies the width (in characters) of an input field
step	 Specifies the legal number intervals for an input field
value	Specifies the default value for an input field




Restricții pentru elementele <input>:

Attribute	Description
disabled	Specifies that an input field should be disabled
max	 Specifies the maximum value for an input field
maxlength	Specifies the maximum number of character for an input field
min	 Specifies the minimum value for an input field
pattern	 Specifies a regular expression to check the input value against
readonly	Specifies that an input field is read only (cannot be changed)
required	 Specifies that an input field is required (must be filled out)
size	Specifies the width (in characters) of an input field
step	 Specifies the legal number intervals for an input field
value	Specifies the default value for an input field



Aplicații interfețe grafice tip formulare

Aplicația 1: Creați o interfață grafică de tip formular on line utilizând HTML5 și CSS, care să aibă designul de mai jos și câmpurile specificate :



The image shows a web form with the following fields and buttons:

- Nume și Prenume* (Text input)
- Adresa (Text input)
- Telefon* (Text input)
- E-mail* (Text input)
- Mesaj* (Text area)
- Trimite (Submit button)
- Reset (Reset button)



Aplicații interfețe grafice tip formulare

Aplicația 2: Realizați un formular on line, utilizând unul dintre link-urile de mai jos:

- <https://www.google.com/drive/> (formular on line)
- <http://www.formulareonline.ro/> (formular de contact, chestionar, formular de comandă)
- <http://smartworks.3x.ro/cv/index.php> (CV)
- <http://www.surveymonkey.com> (chestionare)
- <http://freeonlinesurveys.com/previewsurvey.asp#0> (chestionare)
- <http://www.smart-survey.co.uk/sample-surveys.aspx> (chestionare)